

website:http://us.lge.com 2 1-800-243-0000

24 HOURS A DAY, 7 DAYS A WEEK FOR LG CUSTOMER SERVICE Servicio LG(Atención al Cliente) 24 horas al día, 7 días a la semana

LSC27926ST LSC27926SB LSC27926TT LSC27926SW

SXS REFRIGERATOR

Owner's Manual

Please read this guide thoroughly before operating and keep it handy for reference at all times.

REFRIGERADOR SXS

Manual de Usuario

Lea detenidamente estas instrucciones antes utilizar el refrigerador y guárdelas como referencia para el futuro.

	Table of Contents	
Introduction	Entry	3
	Important Safety Instruction	
	Identification of Parts	
Installation	Where to install	6
Installation	Door Removal	
	Door Replacement	0
	-	
	Water Pipe Installation	
	Water Connection Instruction Guide	
	Operation Instruction Guide	
	Height Adjustment	12
Operation	Starting	13
	Adjusting the Temperatures and functions (Dispenser/Automatic Icemaker)	13
	Shelf	19
	Sich	
	Wine Holder (Applicable to some models only)	
	Egg Bin (Applicable to some models only)	
	Humidity Control in the Vegetable Compartment	19
Suggestion on	Location of Foods	20
Food Storage	Storing Foods	21
Care and	How to Dismantle Parts	22
Maintenance	General Information	24
	Cleaning	24
	Troubleshooting	

Entry

The model and serial numbers are found on the inner case or back of refrigerator compartment of this unit. These numbers are unique to this unit and not available to others. You should record requested information here and retain this guide as a permanent record of your purchase. Staple your receipt here.

Date of purchase
Dealer:
Dealer address:
Dealer phone no.
Model no.:

Serial no .:

Important safety Instructions



This guide contains many important safety messages. Always read and obey



This is the safety alert symbol. It alerts you to safety messages that inform you of hazards that can kill or hurt you or others, or cause damage to the product.

All safety messages will be preceded by the safety alert symbol and the hazard signal word DANGER, WARNING, or CAUTION. These words mean:



ER You <u>will</u> be killed or seriously injured if you don't follow instructions.



WARNING You <u>can</u> be killed or seriously injured if you don't follow instructions.



CAUTION Indicates an imminently hazardous situation which, if not avoided, <u>may</u> result in minor or moderate injury, or product damage only.

All safety messages will identify the hazard, tell you how to reduce the chance of injury and tell you what can happed if the instructions are not followed.

To reduce the risk of fire, electric shock or injury to persons when using your product, basic safety precautions should be followed, including the following. Read all instructions before using this appliance:

- NEVER unplug your refrigerator by pulling on the power cord. Always grip the plug firmly and pull it straight out from the outlet.
- Repair or replace inmediately all electric service cords that have become frayed or otherwise damaged. Do not use a cord that shows cracks or abrasion damage along its length or at either the plug or connector end.
- When moving your refrigerator away from the wall, be careful not to roll over or damage it in any way.
- Do not crush or damage the water line.
- Do not store or use gasoline or other flammable vapors and liquids in the vicinity of this or any other appliance.
- Do not allow children to climb, stand, or hang on the refrigerator doors or shelves in refrigerator. They could damage the refrigerator and seriously injure themshelves.
- Keep fingers out of "pinch point" areas; clearances between the doors and cabinet are necessarily small. Be careful when you open the doors when children are in the area.
- Unplug your refrigerator before cleaning or making any repairs.
- NOTE: We strongly recommend that any servicing be performed by a qualified individual.


Introduction	
	 Before replacing a burned-out light bulb, unplug the refrigerator or turn off power at the circuit breaker or fuse box in order to avoid contact with a live wire filament. (A burned-out light bulb may break when being replaced). NOTE: Setting either or both controls to the OFF position does not remove power to the light circuit. Do not store bottles in the freezer compartment they may break when frozen, causing damage. The refrigerator-freezer should be so positioned that the supply plug is accessible for quick disconnection when accident happens. For personal safety, this appliance must be properly grounded. Have the wall outlet and the circuit checked by a qualified electrician to make sure the outlet is properly grounded. This refrigerator must be properly installed in accordance with the Attention Installer Instructions that were taped to the front of the refrigerator. After your refrigerator is in operation, do not touch the cold surfaces in the freezer compartment when hands are damp or wet. Skin may adhere to the extremely cold surfaces. In refrigerators with automatic icemakers, avoid contact with the moving parts of the ejector mechanism, or with the heating element that releases the cubes. DO NOT place fingers or hands on the automatic icemaking mechanism while the refrigerator is plugged in. DO NOT refreeze frozen foods which have thawed completely. The United States Department of Agriculture in Home and Garden Bulletin No. 69 says: "You may safely refreeze frozen foods that have any off-odor or off-color should not be frozen and should not be eaten. Thawed ice cream should be discarded. If the odor or color of any food is poor or questionable, get rid of it. The food may be dangerous to eat." "Even partial thaving and refreezing reduces the eating quality of foods, particularly fruits, vegetables and prepared foods.
DANGER	Child entrapment and suffocation are not problems of the past. Junked or abandoned refrigerators are still
Risk of child entrapment	dangerous even if they will sit for "just a few days".
	BEFORE YOU THROW AWAY YOUR OLD REFRIGERATOR OR FREEZER
	 Take off the doors. Leave the shelves in place so that children may not easily climb inside.
CFC DISPOSAL	Your old refrigerator may have a cooling system that used CFCs (chlorofuorocarbons). CFCs are believed to harm stratospheric ozone. If you are throwing away your old refrigerator, make sure the CFC refrigerant is removed for proper disposal by a qualified servicer. If you intentionally release this CFC refrigerant, you can be subject to fines and imprisonment under

provisions of environmental legislation. This appliance contains fluid (refrigerant, lubricant), is made of parts and materials which are reusable and / or recyclable. All the important materials should be sent to the collection center of waste material and can be reused after rework (recycling). For take back, please contact with the local agency. GROUNDING IMP REQUIREMENTS TO

IMPORTANT: Please read carefully TO CONNECT ELECTRICITY



Electrical Shock Hazard FOR PERSONAL SAFETY, this appliance must be properly grounded. Have the wall outlet and the circuit checked by a qualified electrician to make sure the outlet is properly grounded.



RECOMMENDED GROUNDING METHOD

The refrigerator should always be plugged into its own individual properly grounded electrical outlet rated for 115 Volts, 60 Hz, AC only and fused at 15 or 20 amperes. This provides the best performance and also prevents overloading house wiring circuits which could cause a fire hazard from overheated wires. It is recommended that a separate circuit serving only this appliance be provided. Use a receptacle which cannot be turned off with a switch or pull chain. Do not use an extension cord.

Where a standard two-prong wall outlet is encountered, it is your personal responsibility and obligation to have it replaced with a properly grounded three-prong wall outlet.

Do not, under any circumstances, cut or remove the third (ground) prong from the power cord.

NOTE: Before performing any type of installation, cleaning, or removing a light bulb, turn the control (Thermostat, Refrigerator Control or Freezer Control, depending on the model) to OFF and then disconnect the refrigerator from the electrical source. When you are finished, reconnect the refrigerator to the electrical source and reset the control (Thermostat, Refrigerator Control or Freezer Control, depending on the model) to the desired setting.


USE OF EXTENSION CORDS

Because of potential safety hazards under certain conditions, we strongly recommend against the use of an extension cord. However, if you still elect to use an extension cord, it is absolutely necessary that it be a UL-listed (in the United States), 3-wire grounding type appliance extension cord having a groundind type plug and outlet, and that the electrical rating of the cord be 15 amperes (minimum) and 120 volts.

Use of an extension cord will increase the clearance needed for the back of the refrigerator.

If the supply cord is damaged, it must be replaced by the manufacturer or its service agent or a similarly qualified person in order to avoid any hazard.

Identication of Parts



Lower Cover

Strong


and even floor


• If you find some parts missing from your unit, they may be parts only used in other models.

Where to install

Unstable installation may cause vibration and noise. If the floor to install the refrigerator on is not even, make the refrigerator level by rotating the height adjusting screw. Carpet or floor covering on which a refrigerator is installed may be discolored by heat from the bottom of the refrigerator. If our refrigerator causes this kind of damage, there is something wrong with it. Customers will not stand for this.

A proper distance from adjacent items Please keep the refrigerator at a proper distance from other things. Too small a distance from adjacent items may result in lowered freezing capability and increased electricity charges consumption.





Where water supply can be easily connected in a dry place

Where it is free

from heat

Select a place where a water supply can be easily connected between the automatic ice maker and dispenser.

Installing the refrigerator in a wet or damp area may cause rust and may be an electrical hazard.

If this refrigerator is installed where the

electricity used increases.

ambient temperature is high, the freezing capacity is deteriorated and the cost of




NOTE

- Install the refrigerator at a place where the ambient temperature is $5^{\circ}C \sim 43^{\circ}C$ ($41^{\circ}F \sim 110^{\circ}F$).

Ambient temperature outside this range may cause product malfunction. Also, the tube between the dispenser and automatic ice maker may freeze.

- Method to remove protection film(Some Model)
- 1. Grasp the handles with both hands and push them upward to remove.
- 2. Entirely remove the protection film adhered to the external surface of the door.
- 3. Assemble the fixing bracket on both ends of the handle to the fixing bolt of the door and lower the handle downward until it is entirely fixed.



7

Door removal

N Warning	Electric Shock Hazard Disconnect electrical supply to refrigerator before installing. Failure to do so could result in death or serious injury. If your entrance door is too narrow for the refrigerator to pass through, remove the refrigerator door and pass the refrigerator laterally.
Remove Lower Cover and Water Feed Tube	Remove the lower cover by lifting upward, and then pull up the water feed tube while pressing area ① shown in the figure to the right.
	 NOTE If a tube end is deformed or abraded, trim the part away. Disconnecting the tube under the door causes about 1.5 litters water to flow out. Please put up a big container to prevent it.
Remove the Freezer Compartment Door	1) Remove the hinge cover by loosening the screws. Disconnect all connections except the ground line.
	2) Remove the keeper by rotating it counter clockwise ① and then lifting the upper hinge up ②.
	NOTE • When removing the upper hinge, be careful that the door does not fall forward .
	3) Remove the freezer compartment door by lifting it upward. This time, the door should be lifted enough for the water feed tube to be completely pulled out.
	NOTE • After removing the door, take it into the kitchen where you are installing the refrigerator. Lay it down on a blanket and be careful to avoid damaging the water feed tube.
Remove the Refrigerator Door	1) Loosen the hinge cover screws and remove the cover. Remove connection wire, if any, except for the ground line.
	2) Remove keeper by rotating it clockwise ① and then remove the upper hinge by lifting it up ②.
	3) Remove the refrigerator compartment door by lifting it up.
8	

Move the Refrigerator

Push the refrigerator sideways through the entrance door as shown in the right picture.

Door replacement


Mount the doors in the reverse order of removal after the refrigerator is brought to the installation area.



NOTE:

Correct

Check the direction of the lever hinge.



Feed water tube installation

Before Installation

- Automatic icemaker operation needs water pressure of 21.3~121psi(lb/inch²) (That is, a 7oz. paper cup will be filled within 3 sec.).
- If water pressure does not reach the rated 21.3psi (lb/in² or below), it is necessary to purchase a separate pressure pump for normal automatic icemaking and cool water feed.
- Keep the total length of the water feed tube within 40 feet and be careful not to bend or kink the tube. If the tube is longer than 40 feet, the icemaker and water dispenser will not operate properly.
- Install the water feed tube at a place free from heat.

Refer to instructions with water filter kit for installation.

to the OFF position to prevent operation without water.

Water Connection Instruction Guide

• Connect to potable water supply only.

Read all directions carefully before you begin.

· Use copper tubing and check for leaks.

Warning

Connecting the Refrigerator to a Water Source

Tools Required

Screwdriver

Standard screwdriver

IMPORTANT

7/16-inch and 1/2-inch open-end wrenches or two adjustable wrenches

· It may take up to 24 hours for your icemaker to begin producing ice.

· If operating the refrigerator before installing the water connection, turn icemaker

· All installations must be in accordance with local plumbing code requirements.

· Install copper tubing only in areas where temperatures will remain above freezing.

- 1/4-inch nut driver
- 1/4-inch drill bit
- Hand drill or electric drill (properly grounded)

NOTE

• Your refrigerator dealer has a kit available with a 1/4-inch saddle-type shut-off valve, a union, and copper tubing. Before purchasing, make sure a saddle-type valve complies with your local plumbing codes. Do not use a piercing-type or 3/16-inch saddle valve which reduces water flow and clogs more easily.

Electric drill


Adjustable wrenches

Connect the Tubing to Water Line

- 1. Unplug refrigerator or disconnect power.
- 2. Turn OFF main water supply. Turn on the nearest faucet to relieve the pressure on the line. It may help to open an outside faucet to allow the water to drain from the line in the house.
- 3. Find a 1/2-inch to 1-1/4-inch vertical COLD water pipe near the refrigerator.

NOTE

- Horizontal pipe will work, but the following precaution must be taken: Drill on the top of the pipe, not the bottom. This will help keep water away from the drill. This also keeps normal sediment from collecting in the valve.
- 4. To determine the length of copper tubing you will need, measure from the connection on the lower left rear of the refrigerator to the water pipe. Add 7 feet (2.1m) to allow for moving refrigerator for cleaning. Use 1/4-inch O.D. (outside diameter) copper tubing. Be sure both ends of copper tubing are cut square.
- 5. Using a drill, drill a 1/4-inch hole in the cold water pipe you have selected.
- 6. Fasten shut-off valve to cold water pipe with pipe clamp. Be sure outlet end is solidly in the 1/4-inch drilled hole in the water pipe and that the washer is under the pipe clamp. Tighten packing nut. Tighten the pipe clamp screws carefully and evenly so washer makes a watertight seal. Do not overtighten or you may crush the copper tubing, especially if soft (coiled) copper tubing is used. Now you are ready to connect the copper tubing.
- 7. Slip compression sleeve and compression nut on copper tubing as shown. Insert end of tubing into outlet end squarely as far as it will go. Screw compression nut onto outlet end with adjustable wrench. Do not over tighten.
- 8. Place the free end of the tubing into a container or sink, and turn ON main water supply and flush out tubing until water is clear. Turn OFF shutoff valve on the water pipe. Coil the copper tubing as shown below.



	Operation Instruction Guide			
Connect the Tubing to the Refrigerator	Before making the connection to the refrigerator, be sure the refrigerator power cord is not plugged into the wall outlet.			
	If your refrigerator does not have a water filter, we recommend installing one. If your water supply has sand or particles that could clog the screen of the refrigerator's water valve. Install the filter in the water line near the refrigerator.			
	1. Remove the plastic flexible (sleeve)			
	2. Place the compression nut and ferrule (sleeve) onto the end of the tubing as shown.			
	Insert the end of the copper tubing into the connection as far as possible. While holding the tubing, tighten the fitting.			
Turn the Water On at	Tighten any connections that leak.			
the Shutoff Valve	 Plug In the Refrigerator Arrange the coil of copper tubing behind the refrigerator so it does not vibrate against the back of the refrigerator or against the wall. Push the refrigerator back to the wall. 			
	 Start the Icemaker Set the icemaking stop switch to the ON position The icemaker will not begin to operate until it reaches its operating temperature of 15 °F (-9 °C). It will then begin operation automatically if the icemaking stop switch is in the ON position. 			
Automatic Ice maker	But these quantities may vary according to circumstance, including ambient temperature, door openings, freezer load etc.			
	The Icemaker stops when the bin is full.			
	NOTE It takes about 12 hours for a newly installed refrigerator to make ice. It is normal to hear a noise when ice drops into the bin.			
	 The first ice and water may include particles or odor from the feed water pipe or feed water box. Throw away the ice. This is also necessary if the refrigerator has not been used for a long time. 			
	- Never store beverage cans or other foods in ice storage bin for the purpose of rapid cooling. Such actions may damage the automatic ice maker.			
	- Never remove the icemaker cover.			
	- Shake the bin occasionally to cause the ice to settle.			
G	- Ice may pile up just around the icemaker causing the icemaker to think that the ice storage bin is full.			
	- If discolored ice is dispensed, contact an Authorized Service Center immediately. Do not use the ice or water until the problem is corrected.			

Installation

If the freezer compartment door is lower than the refrigerator compartment door

If the freezer compartment door is higher than the refrigerator compartment door

-Type 1

If the freezer compartment door is higher than the refrigerator compartment door

-Type 2




After leveling the door height


Height adjustment

(First identify your adjusting screw type, it could vary)


Make them level by inserting flat (- type) driver into the groove of the left height adjusting screw and rotating it clockwise (0). Height difference



Make them level by inserting flat (- type) driver into the groove of the right height adjusting screw and rotating it cbckwise (①).



Adjust the level when the refrigerator door is lower than the freezer door during the use of the refrigerator.



- 1. Using the wide side of the tool for adjustment (3), turn the keeper nut (2) () clockwise to loosen the keeper nut.
- 2. Using the narrow side of the tool for adjustment, turn the adjustment hinge pin ② () clockwise or () counterclockwise to level the refrigerator and freezer door.
- 3. After setting the level of the door, turn the keeper nut(.______) counterclockwise to tighten.

Do not force too hard to level the height. The hinge pin can be pulled out. (Adjustable range of height is a maximum of 2" (5 cm).

The refrigerator door will close smoothly by raising the front side by adjusting the height adjusting screw. If the door does not close properly because it is improperly adjusted, the performance of the refrigerator will be affected.

12

Starting

When your refrigerator is first installed, allow it to stabilize at normal operating temperatures for 2-3 hours prior to filling it with fresh or frozen foods. If operation is interrupted, wait 5 minutes before restarting.

Adjusting The Temperatures and Functions Water/Ice Output Dispenser Push Switch **Dispenser** Lamp (Bottom ceiling of function display board) Function display board Ë \triangleleft REFRIGERATOR LIGHT/FILTER ALARM/LOCK 3SECS ICE PLUS DISPENSER **Display Power** Change Display Degree Saving Mode Fahrenheit Centigrade Mode

NOTE:

Your model may not include every option.

The control display is operated by touch. Excessive moisture on the display may cause a malfunction. Please keep display clean and dry.

1. Display Power Saving Mode This function places the display into power saving mode until the next time the door is opened.

Press the FREEZER and ICE PLUS buttons simultaneously and hold them for 5 seconds until the Ding sounds. All LEDs will then turn ON, then OFF. When the power saving mode is activated, the display will remain off until the next time the door is opened. Then, it will come on whenever a door is opened or a button is pressed and remain on for 20 seconds after the last door opening or button selection. To deactivate the power saving mode, press the FREEZER and ICE PLUS buttons simultaneously and hold them for 5 seconds until the Ding sounds.

2. To change temperature display from Fahrenheit to Celsius press and hold FREEZER and REFRIGERATOR buttons simultaneously for more than 5 seconds. Do the same to convert back to Celsius.

You can adjust temperature of freezer compartment and refrigerator Compartment.

Freezer Compartment temperature adjustment



Refrigerator Compartment

temperature adjustment





- * To adjust the temperature in the refrigerator compartment, press the REFRIGERATOR button to cycle through the settings of MEDIUM \rightarrow COLDER \rightarrow COLDEST \rightarrow COOL \rightarrow COOLER.
 - The actual inner temperature varies depending on the food status, as the indicated setting temperature is the target temperature, not actual temperature within refrigerator.
 - Please adjust temperature as above after using refrigerator for minimum 2~3 days.

How to adjust the temperature in the freezer compartment

How to adjust the temperature in the refrigerator compartment

How to use dispenser

 Select among crushed ice, water, and cubed ice and press the push switch with a glass or other container.

Crushed Ice

Light the crushed ice lamp by pressing the selection button.

• Crushed ice will be dispensed by pressing the push switch with a glass.

Water


Light the water lamp by pressing the selection button.

• Water will be dispensed by pressing the push switch with a glass.

Cubed Ice

Light the cubed ice lamp by pressing the selection button.

• Cubed ice will be dispensed by pressing the push switch with a glass.



• Reference : Hold your cup in place for a couple of seconds after dispensing ice or water so the last few drops go in to your cup instead of the floor.

Automatic Icemaker

• The automatic icemaker can automatically make 8 cubes at a time, 120~150 pieces per day. This quantity may vary by circumstance, including ambient temperature, door opening, freezer load. etc.

- Icemaking stops when the ice storage bin is full.
- If you don't want to use automatic icemaker, turn the icemaker switch to OFF. If you want to use automatic ice-maker again, change the switch to ON. To switch ON/OFF follow steps 1 & 2 in the picture.



Operation			
When ice dispensing does not operate smoothly	 Ice is lumped together If the ice lumps together, take it out, break it apart, and put it back into the storage bin. When the icemaker produces too small or lumped together ice, the amount of water supplied to the ice maker needs to adjusted. Contact the service center. If ice is not used frequently, it may lump together. Power failure Water may drop from the refrigerator. Take the ice storage bin out and discard all the ice then dry it and place it back. After the power is restored, the refrigerator defaults to crushed ice. 		
	The unit is newly installed		
M Warning	 It takes about 12 hours for a newly installed refrigerator to make ice. Do not place your hands into the water & ice dispenser opening. Doing so can result in amputation or cuts. 		
Ice plus/Jet freezer	<text><list-item><list-item><list-item><list-item><list-item><list-item></list-item></list-item></list-item></list-item></list-item></list-item></text>		

Lock	 This button stops operation of different button and dispenser function. Locking or Release is repeated whenever the other button and seconds. If you use the ALARM/LOCK button, none of the other buttons will work until you unlock them.
Door alarm	 Door open warning A warning tone will sound 3 times at thirty-second intervals if the refrigerator or freezer door is left open for more than sixty seconds. Please contact with the local service center if warning continue to sound even after closing the door.
Filter condition filter replacement cycle display function	 There is a replacement indicator light for the water filter cartridge on the dispenser. The water filter should be replaced every six months. The filter light comes on to let you know when to replace filter. After replacing the filter, press and hold the filter button more than 3 seconds to reset the indicator.
Dispenser light	 This button turn the dispenser light in the dispenser on an off. The dispenser light function is turned ON or OFF by pressing Light/Filter button. If the dispenser light stays on for more than 7 minutes, it will turn off automatically. Some models have an auto mode that uses a light sensor to turn the dispenser light on and off. Auto light is not applicable to all models.


0	\mathbf{n}	ra	+i	\sim	n
U	DE	ld	UI	Ο	

Other functions	 Ambient Temperature Display Window. Temperature is displayed only between 16 °F ~ 120 °F (-9 °C ~ 49 °C). Temperature less than 15 °F (-9 °C) is indicated with LO and temperature more than 121 °F (49 °C) is indicated with HI. 	
	Diagnostic (failure detection) function	
	The diagnostic function automatically detects failure when failure is found in product during the use of refrigerator.	
	 If your refrigerator fails, do not turn off the power. Call 1-800-243-0000 24/7 and select the option to locate an authorized servicer or call our support line for assistance. Turning off the appliance will make it more difficult for the service technician to determine the problem. 	
How ice/cold water is supplied	Water is cooled while stored in the water tank in freezer door, and then sent to the dispenser.	
	Ice is made in the automatic icemaker and sent to the dispenser.	
Cautions	Throw away the ice (about 20 pieces) and water (about 7 glasses) first made after refrigerator installation. This is also necessary when the refrigerator has not been used for a long time.	
	Keep children away from the dispenser. Children may play with or damage the controls.	
	Be careful that food does not block the ice passage. If foods are placed at the entrance of ice passage, the dispenser may malfunction. The passage may also become blocked with frost if only crushed ice is used. Remove the frost that accumulates.	
	Storing cans or other items in the ice bin may damage the icemaker or the container may burst.	
	Never use thin crystal glass or crockery to collect ice. Such glasses or containers may be broken, and glass fragments could be in the ice.	
	Put ice first into a glass before filling water or other beverages. Water may be splashed if ice is added to existing liquid in a glass.	
	Keep your hands out of the ice door and passage. You might break something or injure yourself.	
	Never remove the ice maker cover.	
	Shake the ice bin occasionally to level the ice in it. Sometimes the ice piles up near the icemaker, causing the icemaker to misinterpret the bin level and stop producing ice.	
	Never use too narrow or deep glass. Ice may be jammed in the ice passage and, thus, the refrigerator may fail.	
	Keep the glass at a proper distance from ice outlet. A glass too close to the outlet may prevent ice from coming out.	

Shelf

Shelf Height Adjustment The refrigerator compartment shelf is movable so that you can place it at a height according to space requirement of foods.

- Slide Shelf Pull the shelf ahead and take it off while lifting both, front and rear part.
- Fix Shelf, Folding Shelf Lightly lift up the front part of shelf to pull it ahead and then take it off while lifting the rear part of shelf.




NOTE

• Make sure the shelf is horizontal. If not, it may drop.

Wine Holder (Applicable to some models only)


Wine Holder Adjustment

Bottles can be stored on their sides in this wine rack. It can be mounted only at the SLIDE SHELF. Move to left to pull out after lifting slightly.




Egg Bin (Applicable to some models only)

You can place the egg box wherever you want it.



[Normal]




NOTE


- Never use the egg box as ice storage bin. It can be broken.
- Never store egg box in the freezer or fresh compartment.
- [For Many Eggs]

Humidity control in the vegetable compartment

The humidity can be controlled by adjusting the humidity control switch to the left or right when storing vegetables or fruits.


High humidity





	Location of Foods (Refer to Identification of Parts)	
Wine Holder	Store wine.	
Snack Drawer	Store small foods such as bread, snacks, etc.	
Freezer Compartment Shelf	Store various frozen foods such as meat, fish, ice cream, frozen snacks, etc.	
Freezer Compartment Door Rack	 Store small packed frozen food. Temperature is likely to increase as door opens. So, do not store long-term food such ice cream, etc. 	
Freezer Compartment Drawer	 Store meat, fish, chicken, etc. after wrapping them with thin foil. Store dry. 	
Milk Product Corner	Store milk products such as butter, cheese, etc.	
Egg Bin	Place this egg box in the proper location.	
Refreshment Center	Store foods of frequent use such as beverage, etc.	
Refrigerator Compartment Shelf	Store side dishes or other foods at a proper distance.	
Refrigerator Compartment Door Rack	Store small packed food or beverages such as milk, juice, beer, etc.	
Vegetable Drawer	Store vegetables or fruits.	

20



	Storing Foods
	 Store fresh food in the refrigerator compartment. How food is frozen and thawed is an important factor in maintaining it's freshness and flavor. Do not store food which spoils easily at low temperatures, such as bananas and melons. Allow hot food to cool prior to storing, placing hot food in the refrigerator could spoil other food, and lead to higher energy consumption. When storing the food, cover it with vinyl wrap or store in a container with a lid. This prevents moisture from evaporating, and helps food to keep its taste and nutrients. Do not block air vents with food. Smooth circulation of chilled air keeps refrigerator temperatures even. Do not open the door frequently. Opening the door lets warm air enter the refrigerator, and cause temperatures to rise. Never keep too much food in door rack because they may be push against the inner racks and could not be fully closed.
Freezer Compartment	 Do not store bottles in the freezer compartment - they may break when frozen. Do not refreeze food that has been thawed. This causes loss of taste and nutrient. When storing frozen food like ice cream for a long period, place it on the freezer shelf, not in the door rack. Do not touch the cold foods or containers- especially made of metal -, with wet hands and place glass products in the freezer compartment. That's why you may have chilblains and they may be broken when their inner matters are frozen, causing personal injury.
Refrigerator Compartment	<list-item><list-item><list-item></list-item></list-item></list-item>

	How to Dismantle Parts		
	 NOTE Dismantling is done in the reverse sequence of assembly. Be sure to unplug the power plug before dismantling and assembly. Never apply severe force to dismantle parts. Parts may be damaged. 		
Freezer Compartment Lamp	Separate the lamp by pulling it out ③ while slightly striking ① and rotating ② the lamp cover. Turn the bulb counterclockwise. Max. 40 W bulb for refrigerator is used and can be purchased at a service center.		
Dispenser Lamp	Seperate the lamp by pulling it out, and then remove the lamp. Max. 15 W bulb for refrigerator is used and can be purchased at a service center.		
Freezer Compartment Shelf	To remove a shelf, lift the left part of the shelf a bit, push it to the direction \mathbb{O} , lift the right part to the direction \mathbb{Q} , and take it out.		
Door Rack and Support	Lift the door rack holding both sides $\ensuremath{\mathbbm O}$ and pull it out to $\ensuremath{\mathbbm O}$ direction.		
Ice Storage Bin	Lift the ice shelf as shown in the right figure ① and pull it out ②. Hold the ice storage bin as shown in the right figure and pull it out ④ while slightly lifting it ③.		
	 To assemble the ice storage bin, push it (6) while slightly lifting it (5). It is recommended not to dismantle the ice storage bin unless it is necessary. Use both hands to remove the ice bin to avoid dropping it. If the ice bin does not slide into place easily, twist the drive device slightly. 	a contraction of the second se	
After Dispenser Is Used	The water collector has no self-draining function. It should be cleaned regularly. Remove the cover by pulling the front side of water collector cover and dry it with a cloth.		
2	2		

To remove the lamp cover, press the protrusion under the lamp cover to the front and then pull the lamp cover out. Turn the bulb counterclockwise. Max. 40 W bulb for refrigerator is used and can be purchased at a service center. NOTE • Be sure to remove parts from the refrigerator door when removing the vegetable compartment, snack drawer, and refreshment center cover.	
 It is recommended that you replace the filter when the water filter indicator light turns on or your water dispenser or ice maker decreases noticeably. After changing the water filter cartridge, reset the water filter status display and indicator light by pressing and holding the BUTTON for 3 seconds. 1) Remove the old cartridge. Rotate the knob of the cartridge counter clockwise. When the cartridge is removed, you will feel it click out of place. Pull out the cartridge. 	
 NOTE Replacing filter causes small amount of water(around 25cc) to flow out. Please put up a cup under the hole to prevent it. 2) Replace with a new cartridge. Take the new cartridge out of it's packaging and remove protective cover from the o-rings. With cartridge knob in the vertical position, push the new filter cartridge into the cover until it stops. If you can't turn the filter from side to side, it isn't fully inserted. Push it in firmly and twist it into place. You will hear the snap when it clicks into place. Using it's handle, twist the cartridge clockwise about 1/4 turn. You will hear the snap when it clicks into place. 3) Flushing the Water System After Replacing Filter. Dispense water through the water dispenser for 3 minutes to purge the system. 	

General Information

Vacation Time	During average length vacations, you will probably find it best to leave the refrigerator in operation. Place freezable items in freezer for longer life. When you plan to store the refrigerator, remove all food, disconnect the power cord, clean the interior thoroughly, and Block the doors open to prevent mold and mildew. Be certain the stored refrigerator does not present a child entrapment danger.	
Power Failure	Most power failures that are corrected in an hour or two will not affect your refrigerator temperatures. However, you should minimize the number of door openings while the power is off.	
lf You Move	Remove or securely fasten down all loose items inside the refrigerator. To avoid damaging the height adjusting screws, turn them all the way into the base.	
Anti- Condensation Pipe	The outside wall of the refrigerator cabinet may sometimes get warm, especially just after installation. Don't be alarmed. This is due to the anti-condensation pipe, which pumps hot refrigerant to prevent sweating on the outer cabinet wall.	
	Cleaning	
	It is important that your refrigerator be kept clean to prevent undesirable odors. Spilled food should be wiped up immediately, since it may acidify and stain plastic surfaces if allowed to settle.	
Exterior	Use a lukewarm solution of mild soap or detergent to clean the durable finish of your refrigerator. Wipe with a clean damp cloth and then dry.	
Interior	Regular cleaning is recommended. Wash all compartments with a baking soda solution or a mild detergent and warm water. Rinse and dry.	
After Cleaning	Please verify that the power cord is not damaged, power plug is not overheated, or power plug is well inserted into the power consent.	
A Warning	Always remove power cord from the wall outlet prior to cleaning in the vicinity of electrical parts (lamps, switches, controls, etc.). Wipe up excess moisture with a sponge or cloth to prevent water or liquid from getting into any electrical part and causing an electric shock. Never use metallic scouring pads, brushes, coarse abrasive cleaners, strong alkaline solutions, flammable or toxic cleaning liquids on any surface. Do not touch frozen surfaces with wet or damp hands, because damp object will stick or adhere to extremely cold surfaces.	



Troubleshooting

Before calling for service, review this list. It may save you both time and expense. This list includes common occurrences that are not the result of defective workmanship or materials in this appliance.

Occurrence

Possible cause

Solution

Running of refrigerator

Refrigerator compressor does not run.	Refrigerator control is off.	Set refrigerator control. See setting the controls.
	Refrigerator is in defrost cycle.	This is normal for a fully automatic defrosting refrigerator. The defrost cycle occurs periodically.
	Plug at wall outlet is disconnected.	Make sure plug is tightly pushed into outlet.
	Power outage. Check house lights.	Call local electric company.
Refrigerator runs too much	Refrigerator is larger than the previous one you owned.	This is normal. Larger, more efficient units run longer in these conditions.
or too long	Room or outside weather is hot.	It is normal for the refrigerator to work longer under these conditions.
	Refrigerator has recently been disconnected for a period of time.	It takes some hours for the refrigerator to cool down completely.
	Large amounts of warm or hot food may have been stored recently.	Warm food will cause the refrigerator to run longer until the desired temperature is reached.
	Doors are opened too frequently or too long.	Warm air entering the refrigerator causes it to run longer. Open the door less often.
	Refrigerator or freezer door may be slightly open.	Make sure the refrigerator is level. Keep food and containers from blocking door. See Troubleshooting section OPENING/CLOSING of doors.
	Refrigerator control is set too cold.	Set the refrigerator control to a warmer setting until the refrigerator temperature is satisfactory.
	Refrigerator or freezer gasket is dirty, worn, cracked, or poorly fitted.	Clean or change gasket. Leaks in the door seal will cause refrigerator to run longer in order to maintain desired temperatures.
	Thermostat is keeping the refrigerator at a constant temperature.	This is normal. Refrigerator goes on and off to keep the temperature constant.

Occurrence	Possible cause	Solution
Refrigerator compressor does not run.	Thermostat is keeping the refrigerator at a constant temperature.	This is normal. The refrigerator goes on and off to keep the temperature constant.

Temperatures are too cold

Temperature in the freezer is too cold but the refrigerator temperature is satisfactory.	Freezer control is set too cold	Set the freezer control to a warmer setting until the freezer temperature is satisfactory.
Temperature in the refrigerator is too cold and the freezer temperature is satisfactory.	Refrigerator control is set too cold.	Set the refrigerator control to a warmer setting
Food stored in drawers freezes.	Refrigerator control is set too cold.	See above solution.

Temperatures are too warm

Temperatures in the refrigerator or freezer are too warm.	Freezer control is set too warm.	Set the freezer or refrigerator control to a colder setting until the freezer or refrigerator temperature is satisfactory.
	Refrigerator control is set too warm. Refrigerator control has some effect on freezer temperature.	Set the freezer or refrigerator control to a colder setting until the freezer or refrigerator temperature is satisfactory.
	Doors are opened too frequently or too long.	Warm air enters the refrigerator/ freezer whenever the door is opened. Open the door less often.
	Door is slightly open.	Close the door completely.
	Large amounts of warm or hot food may have been stored recently.	Wait until the refrigerator or freezer has a chance to reach its selected temperature.
	Refrigerator has recently been disconnected for a period of time.	A refrigerator requires some hours to cool down completely.
Temperature in the refrigerator is too warm but the freezer temperature is satisfactory.	Refrigerator control is set too warm.	Set the refrigerator control to a colder setting.
2	6	

Possible cause

Solution

Odors in refrigerator

Interior needs to be cleaned.	Clean interior with sponge, warm water and baking soda.
Food with strong odor is in the refrigerator.	Cover food completely.
Some containers and wrapping materials produce odors.	Use a different container or brand of wrapping materials.

Opening/Closing of doors/Drawers

Door(s) will not close.	Food package is keeping door open.	Move packages that keep door from closing.
Door(s) will not close.	Door was closed too hard, causing other door to open slightly.	Close both doors gently.
	Refrigerator is not level. It rocks on the floor when it is moved slightly.	Adjust the height adjusting screw.
	Floor is uneven or weak. Refrigerator rocks on the floor when it is moved slightly.	Be sure floor is level and can adequately support refrigerator. Contact carpenter to correct sagging or sloping floor.
	Refrigerator is touching wall or cabinets.	Move refrigerator
Drawers are difficult to move.	Food is touching shelf on top of the drawer	Keep less food in drawer.
	Track that drawer slides on is dirty.	Clean drawer and track.

Dispenser

Dispenser will not dispense ice	Ice storage bin is empty.	When the first supply of ice is dropped into the bin, the dispenser should operate.
	Freezer temperature is set too warm.	Turn the freezer control to a higher setting so that ice cubes will be made. When the first supply of ice is made, the dispenser should operate.
	Household water line valve is not open.	Open household water line valve and allow sufficient time for ice to be made. When ice is made, dispenser should operate.
	Refrigerator or freezer door is not closed.	Be sure both doors are closed.

Occurrence	Possible cause	Solution
Dispenser will not dispense ice.	Ice has melted and frozen around auger due to infrequent use, temperature fluctuations and/or power outrages.	Remove ice storage bin, and thaw and the contents. Clean bin, wipe dry and replace in proper position. When new ice is made, dispenser should operate.
Ice dispenser is jammed.	Ice cubes are jammed between the ice maker arm and back of the bin.	Remove the ice cubes that are jamming the dispenser.
	Ice cubes are frozen together.	Use the dispenser often so that cubes do not freeze together.
	Ice cubes that have been purchased or made in some other way have been used in the dispenser.	Only the ice cubes made by the ice maker should be used with the dispenser.
Dispenser will not dispense water.	Household water line valve is not open. See problem Icemaker is not making any ice.	Open household water line valve.
	Refrigerator or freezer door is not closed.	Be sure both doors are closed.
Water has an odd taste and/or odor.	Water has been in the tank for too long.	Draw and discard 7 glasses of water to freshen the supply. Draw and discard an additional 7 glasses to completely rinse out tank.
	Unit not properly connected to cold water line.	Connect unit to cold water line which supplies water to kitchen faucet.
Sound of ice dropping	This sound is normally made when automatically made ice is dropped into ice storage bin. Volume may vary according to refrigerator's location.	
Sound of water supply	This sound is normally made when ice maker is supplied with water after dropping the automatically made ice.	
Other	Please thoroughly read Automatic icemaker and dispenser in this manual.	

ONLY IN UNITED STATES CUSTOMER ASSISTANCE NUMBERS:

http://www.lgservice.com

 To Prove Warranty Coverage Retain your Sales Receipt to prove date of purchase.
 A copy of your Sales Receipt must be submitted at the time warranty service is provided.

- To Obtain Product, Customer or Service Assistance Call Toll-free for Customer Service Tel : 1-800-243-0000
- To Obtain Nearest Authorized Service Center
 Call 1-800-243-0000, push option #1, 24 hours a day, 7 days per week.
 Please have your product type (Monitor, TV, VCR, MWO, Refrigerator) and ZIP code ready.

LG ELECTRONICS, INC. LG REFRIGERATOR LIMITED WARRANTY - USA



Your LG Refrigerator will be will repaired or replaced, at LG's option, if it proves to be defective in material or workmanship under normal use, during the warranty period ("Warranty Period") set forth below, effective from the date ("Date of Purchase") of original consumer purchase of the product. This warranty is good only to the original purchaser of the product and effective only when used in the United States, including Alaska, Hawaii, and U.S. Territories.

WARRANTY PERIOD:	HOW SERVICE IS HANDLED:
REFRIGERATOR/FREEZER	In-Home Service (Except Model GR051):
LABOR: One Year from the Date of Purchase.	Please retain dealer's dated bill of sale or delivery
PARTS: One Year from the Date of Purchase.	ticket as evidence of the Date of Purchase for proof of warranty, and submit a copy of the bill of sale to
SEALED SYSTEM (Compressor, Condenser, and Evaporator)	the service person at the time warranty service is provided.
LABOR: One Year from the Date of Purchase.	Please call 1-800-243-0000 and choose the
PARTS: Seven years from the Date of Purchase.	appropriate option to locate your nearest LG Authorized Service Center. (Phones are
Replacement Units and Repair Parts are warranted for the remaining portion of the original unit's warranty period.	answered 24 hours a day, 365 days per year.) Or visit our website at: http://www.lgservice.com

THIS WARRANTY IS IN LIEU OF ANY OTHER WARRANTY, EXPRESS OR IMPLIED, INCLUDING WITHOUT LIMITATION, ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. TO THE EXTENT ANY IMPLIED WARRANTY IS REQUIRED BY LAW, IT IS LIMITED IN DURATION TO THE EXPRESS WARRANTY PERIOD ABOVE. NEITHER THE MANUFACTURER NOR ITS U.S. DISTRIBUTOR SHALL BE LIABLE FOR ANY INCIDENTAL, CONSEQUENTIAL, INDIRECT, SPECIAL, OR PUNITIVE DAMAGES OF ANY NATURE, INCLUDING WITHOUT LIMITATION, LOST REVENUES OR PROFITS, OR ANY OTHER DAMAGE WHETHER BASED IN CONTRACT, TORT, OR OTHERWISE. Some states do not allow the exclusion or limitation of incidental or consequential damages or limitations on how long an implied warranty lasts, so the above exclusion or limitation may not apply to you. This warranty gives you specific legal rights and you may also have other rights that vary from state to state.

THIS LIMITED WARRANTY DOES NOT APPLY TO:

- Service trips to your home to deliver, pick up, and/or install the product, instruct, or replace house fuses or correct wiring, or correction of unauthorized repairs.
- Damages or operating problems that result from misuse, abuse, operation outside environmental specifications or contrary to the requirements of precautions in the Operating Guide, accident, vermin, fire, flood, improper installation, acts of God, unauthorized modification or alteration, incorrect electrical current or voltage, or commercial use, or use for other than intended purpose.
- Repairs when your LG refrigerator is used in other than normal, single-family household use.

The cost of repair or replacement under these excluded circumstances shall be borne by the consumer.

CUSTOMER INTERACTIVE CENTER NUMBERS

To obtain Customer Assistance, Product	Call 1-800-243-0000 (24 hours a day, 365 days per
Information, or Dealer or Authorized Service Center	year) and select the appropriate option from the menu.
location:	Or visit our website at: http://www.lgservice.com

TO CONTACT LG ELECTRONICS BY MAIL:

LG Customer Interactive Center P. O. Box 240007 201 James Record Road Huntsville, Alabama 35824 ATTN: CIC



http://www.lge.com

P/No. 3828JL8797E